TMH-6000/2
AIR HOIST

RED ROOSTER LIFTING

STANDARD FEATURES


- Toku rotary vane motor
- ATEX zone 2 specification
- Robust 3 step planetary gearbox
- Failsafe automatic internal disc brake
- Mechanical upper & lower switches
- Cast steel housing
- Internal silencing down to 80 dB(A)
- Alloy safety swivel hooks with safety catch
- Load chain 13 x 36mm of European manufacture to EN818-7
- Automatic load limiter

AVAILABLE OPTIONS

- Marine specification
- Special paint systems
- Corrosion protection
- ATEX zone 1 specification
- Chain collectors (galvanised or stainless steel)
- Air Service units
- Festoon systems
- Radio control

MODEL	WLL	LIFTING SPEED WITH LOAD	LIFTING SPEED WITHOUT LOAD	LOWERING SPEED WITH LOAD	
TMH-6000/2	6000 kg	2.7 m/min	5.4 m/min	5.1 m/min	
	AIR CONSUMPTION LIFTING	AIR CONSUMPTION LOWERING	AIR CONNECTION	MINIMUM HOSE DIA.	AIR SERVICE
TMH-6000/2	56 l/sec	68 l/sec	1“ BSP	3/4" HOSE	1” FLR
	CHAIN FALLS	WORKING PRESSURE	WEIGHT WITH 3M HOL	ADDITIONAL METRE HOL	
TMH-6000/2	2	4 - 6 bar	124 kg	7.6 kg	

C = CORD CONTROL PE = PENDANT
Speeds at 6 bar



All measurements are in mm
Information subject to change without notice



Image for illustration purposes only

ATEX ZONE 2 AS STANDARD

RED ROOSTER LIFTING
Nauta House, The Meadows
Oldmeldrum, Aberdeenshire
United Kingdom, AB51 0EZ

T: +44 (0) 1651 872101
E: sales@redroosterlifting.com
W: www.redroosterlifting.com